



TYPICAL USES

- Noncorrosive
- Biodegradable
- Highly Concentrated
- Nonflammable
- Free Rinsing

PRODUCT DESCRIPTION

CSL 471 is a concentrated roof cleaner manufactured with high quality detergents. The combination of solvent emulsion and wide dilution range makes

CSL 471 extremely versatile for application on a variety of roof substrates. **CSL 471** is low toxic and free of petroleum solvents.

DIRECTIONS

1. Dilute with water according to soil conditions
2. Dilutions: Light cleaning (1:80, ie. mix 1 part of **CSL 471** with 80 parts of water); Medium cleaning (1:60); Heavy cleaning (1:40); Extremely heavy soil (1:20)
3. Application Method: mop, rag, sponge, sprayer, pressure washer or steam cleaner.
4. Rinse with water or wipe clean with a rag or sponge.

**NOTE: The concentration of CSL 471 is project-specific; higher concentrations may be required for proper cleaning.*

APPLICATION

Aluminum, Cooper, Brass, Stainless Steel, Galvanized Steel, Mod. Bitumen APP, Mod. Bitumen SBS, BUR, TPO, EPDM, Painted Surfaces, Silicone Coated Roof, Acrylic Coated Roof, PU Coated Roof, PU Foam, Ceramic, Brick, Concrete, Exhaust Hoods and Fans, Glass and Plastic. Consult CSL Silicones Inc. for further product compatibility..

SAFETY PRECAUTIONS

This product is intended for use only by professional applicators in accordance with the advice given in this document, the Safety Data Sheet (SDS) and the container(s), and should not be used without reference to the SDS that CSL Silicones Inc. has provided to its customers. **KEEP OUT OF REACH OF CHILDREN.**

All work involving the application and use of this product should be performed in compliance with all relevant national, Health, Safety & Environmental standards & regulations.

If in doubt regarding the suitability of use of this product, consult CSL Silicones Inc. for further advice.

STORAGE

Store in areas that are clean, dry, and free of dust, dirt, and grease.

Shelf Life: 12 months from date of manufacture in the original unopened container below 90°F (32°C). Subject to re-inspection thereafter. Store in dry, shaded conditions away from sources of heat or ignition. May be stored below freezing.

PACKAGING

CSL 471 is available in 4-1 gallon jugs.

WARRANTY

CSL Silicones Inc. warrants that its products will meet its specifications. CSL shall in no event be liable for incidental or consequential damages. Except as expressly stipulated, CSL's liability, expressed or implied, is limited to the stated selling price of any defective goods.

Data is subject to change without notice and it is therefore recommended that this information not be used for specification writing. For additional information on specific applications, contact the manufacturer.

Disclaimer

The information given in this sheet is not intended to be exhaustive and any person using the product for any purpose other than that specifically recommended in this document without first obtaining written confirmation from CSL Silicones Inc. as to the suitability of the product for the intended purpose does so at his/her own risk. The information contained herein has been prepared in good faith to comply with applicable federal and provincial (state) law(s). However, no warranty of any kind is given or implied and CSL Silicones Inc. will not be responsible for any damages, losses or injuries that may result from the use of any information contained herein. While CSL endeavors to ensure all advice it gives about the product (whether in this document or otherwise) is correct, we have no control over either the quality or condition of the substrate or the many factors affecting the use and application of the product. Therefore, unless CSL specifically agrees in writing to do so, it does not accept any liability whatsoever or howsoever arising for the performance of the product, or for any consequential loss or damage arising out of the use of the product. Any warranty, if given or specific Terms & Conditions of Sale are contained in CSL's Terms & Conditions of Sale, a copy of which can be obtained upon request. The information contained herein is liable to modification from time-to-time in light of experience and CSL's policy of continuous product improvement. It is the user's responsibility to check that this document is current prior to using the product. This document must not be used for specification writing.

Technical Data Sheet

CSL Silicones Inc.

144 Woodlawn Rd. W.
Guelph, ON N1H 1B5
Canada

T +1 519.836.9044
TF + 1 800.265.2753

cslsilicones.com

CSL 471 Reviewed May 11, 2026
Document Control Number: PM-102-471-EN
All trademarks registered. All rights reserved.

